

GR 99 P 2739

Description

Method for conditioning a database for automatic speech processing

5

The invention relates to a method for conditioning a database for automatic speech processing, as well as a method for training a neural network for assigning graphemes to phonemes for automatic speech processing, and a method for assigning graphemes to phonemes in the synthesization of speech or in the recognition of speech.

15 It is known to use neural networks for synthesizing speech, the neural networks converting a text, which is represented in a sequence of graphemes, into phonemes which are converted into the corresponding acoustic sounds by an appropriate speech output device. Graphemes are letters or combinations of letters which in each case are assigned a sound, the phoneme. The neural network must be trained before being used for the first time. This is normally performed by using a database which contains the grapheme/phoneme assignments, it being established thereby which phoneme is assigned to which grapheme.

25 The setting up of such a database constitutes a substantial outlay on time and mental effort, since databases of this type can usually only be constructed with the aid of a language expert.

30 The object of the invention is to create a method with the aid of which it is possible in a simple way to set up a database containing grapheme/phoneme assignments.

The object is achieved by means of a method having the features of claim 1. Advantageous refinements of the invention are specified in the subclaims.

- 5 The method according to the invention for conditioning a database for automatic speech processing proceeds from a database which contains words in the form of graphemes and phonemes. Such databases already exist for most languages. These databases are dictionaries
- 10 which contain the words in script (graphemes) and in phonetic transcription (phonemes). However, these databases lack the assignment of the individual phonemes to the corresponding graphemes. This assignment is executed automatically according to the
- 15 invention by means of the following steps:
- a) assigning the graphemes to the phonemes of all the words which have the same number of graphemes and phonemes, the graphemes and phonemes being assigned to
 - 20 one another in pairs,
 - b) assigning the graphemes to the phonemes of all the words which have more graphemes than phonemes, all the graphemes firstly being assigned to the phonemes in pairs until an assignment error arises on the basis of
 - 25 the assignments determined hitherto, or there are present only at the end of the word one or more graphemes to which no phoneme is assigned, and combining a plurality of graphemes to form a grapheme unit and assigning a grapheme to the phoneme unit, and
 - 30 c) assigning the graphemes to the phonemes of all the words which have fewer graphemes than phonemes, a plurality of phonemes being combined to form a phoneme unit, and a single grapheme being assigned to them in such a way that the remaining grapheme/phoneme
 - 35 assignments of the word to be analyzed correspond to the assignments found under a) and b),
 - d) assigning the words hitherto not assignable, the words being examined in terms of the phoneme units determined under c) and/or the grapheme units

GR 99 P 2739

- 2a -

determined under b), and the phonemes are assigned to
the graphemes while taking account

GR 99 P 2739

- 3 -

of the phoneme unit and/or grapheme units, and
there being executed at least after step a) a
correction step with the aid of which assignments of
words which contradict the further assignments
5 determined in step a) are erased.

According to the invention, the first step is to
examine words which have the same number of graphemes
and phonemes. The graphemes of these words are assigned
10 to the phonemes in pairs, the assignments of the words
which contradict the further assignments being erased
in a correction step following thereupon.

A large number of the words can be processed with the
15 aid of this first assignment operation and, in
addition, statistically significant assignments can be
achieved which permit checking in the correction step
and which also permit checking of the further
assignments to be set up in the subsequent steps.

20 Thereafter, those words are examined in the case of
which the number of phonemes differs from the number of
graphemes. In the case of words with more graphemes
than phonemes, a plurality of graphemes are combined to
25 form grapheme units, and phonemes are combined to form
phoneme units in the case of words with fewer graphemes
than phonemes.

After termination of these steps, the words not
30 hitherto assignable are examined, account being taken
in this case of the determined phoneme units and/or the
determined grapheme units.

Consequently, the method according to the invention is
35 used to set up step by step an "assignment knowledge"
which is based initially on pairwise grapheme/phoneme
assignments and into which

grapheme units and phoneme units are also incorporated in the course of the method.

5 The method according to the invention can be applied to any desired language for which there already exists an electronically readable database which contains words in the form of graphemes and phonemes, there being no need for an assignment between the phonemes and graphemes. The use of expert knowledge is not
10 necessary, since the method according to the invention is executed fully automatically.

It is then possible to use the database set up according to the invention to train a neural network
15 with the aid of which the grapheme/phoneme assignments are executed automatically in synthesizing or recognizing speech.

The invention is explained below in more detail with
20 the aid of an exemplary embodiment that is illustrated in the drawings, in which:

Figure 1 shows an exemplary embodiment of the method according to the invention in a flowchart,
25

Figure 2 shows a schematic of a neural network for assigning graphemes to phonemes, and

Figure 3 shows a schematic of a device for carrying
30 out the method according to the invention.

The method according to the invention serves for conditioning a database for speech synthesis, the starting point being an initial database that contains
35 words in the form of graphemes and phonemes. Such an initial database is any dictionary that contains words both in script (grapheme) and in phonetic transcription (phonemes). However, these dictionaries do not contain

GR 99 P 2739

- 4a -

an assignment of the individual graphemes to the
respective phonemes. The purpose and aim of the method

according to the invention is to set up such an assignment.

5 An exemplary embodiment of the method according to the invention is illustrated in a flowchart in figure 1. The method is started in a step S1.

10 Step S2 examines all words that have the same number of graphemes and phonemes. The graphemes of these words are assigned to the corresponding phonemes in pairs.

15 Such a pairwise assignment is executed, for example, for the English word "run", which can be represented in the following way with the aid of its graphemes and phonemes:

Graphemes:	r u n
Phonemes:	r A n

20 In the case of "run", the grapheme "r" is assigned to the phoneme "r", the grapheme "u" to the phoneme "A", and the grapheme "n" to the phoneme "n". In the case of this pairwise assignment, each individual grapheme is therefore respectively assigned to a single phoneme.

25 This is executed for all words that have the same number of phonemes and graphemes.

30 In the subsequent step S3, a correction is executed which erases the assignments of the words that contradict the further assignments determined in step S2. For this purpose, the frequencies of the individual grapheme/phoneme assignments are detected, and grapheme/phoneme assignments which only seldom occur are erased. If the frequency of a specific

35 grapheme/phoneme assignment is below a predetermined threshold value, the corresponding grapheme/phoneme assignments are erased. The threshold value is, for example, in the range of frequency from 10 to 100. The threshold value can be adjusted as appropriate

GR 99 P 2739

- 6 -

depending on the size of the vocabulary of the initial database, a higher threshold value being expedient in the case of larger initial databases than in the case of smaller initial databases.

5

An example of such a contradictory grapheme/phoneme assignment is the English word "fire":

10 Graphemes: f i r e
 Phonemes: f I @ r

15 The assignment of the grapheme "r" to the phoneme "@", and the assignment of the grapheme "e" to the phoneme "r" are incorrect. These two assignments occur very seldom, for which reason their frequency is lower than the threshold value, and so they are erased in step S3. In addition, the word "fire" is marked again in step S3 as non-assigned, so that it can be re-examined in a later assignment step.

20

25 Words which have more graphemes than phonemes are examined in step S4, in each case one grapheme being assigned to one phoneme in the reading direction (from left to right), and the remaining graphemes being combined to form a grapheme unit with the last grapheme that has been assigned to a phoneme. The example of a word that is correctly assigned in this way is the English word "aback":

30 Graphemes: a b a c k
 Phonemes: x b @ k

35 In step S5 following thereupon, a correction is executed in turn with the aid of which assignments are erased that contradict the assignments determined hitherto, that is to say assignments that have only a low frequency. Step S5 is therefore identical to step S3.

GR 99 P 2739

- 7 -

In step S6, the words that have more graphemes than phonemes and could not be correctly assigned in step S4 are examined anew, an individual grapheme being assigned in each case to an individual phoneme in the reading direction (from left to right). Each individual assignment is checked as to whether it corresponds to the assignments determined hitherto. If this checking reviews that a grapheme/phoneme assignment does not correspond to the previous assignments, that is to say does not have the required frequency, the method reverts to the last grapheme/phoneme assignment and joins the grapheme of this grapheme/phoneme assignment to the next grapheme in the reading direction to form a grapheme unit. The remaining phonemes and graphemes are then assigned to one another again individually, each individual grapheme/phoneme assignment being checked, in turn.

One or more grapheme units can be generated inside a word during this method step, the grapheme units comprising two graphemes as a rule. However, it is also possible that the grapheme units can comprise three or more graphemes.

A word in which step S6 leads to a successful assignment is, for example, the English word "abasement":

Graphemes:	a b a s e m e n t
Phonemes:	x b e s m i n t

In the case of "abasement", the pairwise assignment proceeds correctly up to the grapheme "e", which is firstly assigned to the phoneme "m". This assignment contradicts the assignments determined hitherto, for which reason the method converts to the last successful assignment of the grapheme "s" to the phoneme "s", and joins the grapheme "s" with the grapheme "e" to form

GR 99 P 2739

- 7a -

the grapheme unit "se". The further pairwise assignment
of the graphemes

GR 99 P 2739

- 8 -

to the phonemes corresponds again to the assignments determined hitherto, for which reason they are executed correspondingly.

- 5 The words that were examined in step S6 and have not been assigned with complete success are marked in step S7, and their assignments are erased, in turn.

- 10 In step S8, the words that have more graphemes than phonemes and could not be correctly assigned in steps S4 and S6 are examined anew, an individual grapheme being assigned in each case to an individual phoneme firstly in the reading direction (from left to right). Each individual assignment is checked, in turn, as to
15 whether it corresponds to the assignments determined hitherto. If this check shows that a grapheme/phoneme assignment does not correspond to the previous assignments, that is to say that the number of the frequency is below the predetermined threshold value,
20 individual graphemes are assigned to individual phonemes counter to the reading direction (from right to left). If, in the case of this method, only one phoneme is left over that cannot be assigned a grapheme, the remaining graphemes are combined to form
25 a grapheme unit and assigned to the one phoneme.

A grapheme unit can be generated inside a word in this method step.

- 30 A word in the case of which step S8 leads to a successful assignment is, for example, the English word "amongst":

35 Graphemes: a m o n g s t
 Phonemes: x m A G s t

In the case of "amongst", the pairwise assignment from left to right is performed correctly up to the grapheme "n", which is firstly assigned to the phoneme "G". This

GR 99 P 2739

- 8a -

assignment contradicts the assignments determined hitherto, for which reason a pairwise assignment is executed from right to left. This assignment

GR 99 P 2739

- 9 -

proceeds correctly up to the grapheme "g", which is initially assigned to the phoneme "G". This assignment contradicts the assignment determined hitherto. The phoneme "G" is left over as the only phoneme that cannot be assigned to a grapheme. This phoneme "G" is now assigned to the remaining graphemes "n" and "g", which are combined to form a grapheme unit.

The words examined in step S8, which have not been assigned with complete success, are marked in step S9 and their assignments are erased, in turn.

The words that have fewer graphemes than phonemes are examined in step S10, the individual graphemes being assigned in pairs to the individual phonemes, the graphemes also being assigned to the phonemes adjacent to the assigned phonemes. The respective frequency of all these assignments is determined, and if it is established that a grapheme can be assigned to the two adjacent phonemes with a high frequency, these two phonemes are combined to form a phoneme unit if the two phonemes are two vowels or two consonants.

A word in which step S9 leads to a correct assignment is, for example, the English word "axes":

Graphemes: a x e s

Phonemes: @ k s i z

In the case of "axes", the assignments of the grapheme "x" to the phonemes "k" and "s" respectively yields a frequency that is above a predetermined threshold value, so that these two phonemes are combined to form the phoneme unit "ks". The remaining graphemes and phonemes are assigned in pairs, in turn.

It is also possible in step S10 that a plurality of phoneme units are formed, or that the phoneme units also comprise more than two phonemes.

- 5 A correction is carried out in turn in step S11 in the case of which the assignments that seldom occur are erased, and the words in which these contradictory assignments have been established are marked as non-assigned. Step S11 corresponds essentially to steps
- 10 S3 and S5, although in this case account is also taken of the grapheme/phoneme assignments determined up to step S10.
- Step S12 corresponds essentially to step S10, that is
- 15 to say phoneme units are formed from adjacent phonemes, the phoneme units not being limited in step S12 to two consonants or two vowels, but also being capable of containing a mixture of vowels and consonants.
- 20 A correction operation that corresponds to step S11 is carried out in turn in step S13, account being taken of all grapheme/phoneme assignments determined in the interim.
- 25 The phoneme units determined in steps S10 and S12 are used in step S14 in order to re-examine words whose graphemes could not be correctly assigned to the phonemes, use being made, for adjacent phonemes, of a phoneme unit that exists for them already. It is also
- 30 possible as an option to take account of the previously determined grapheme units. Should no use be made of this option, grapheme units can be formed here anew in accordance with the methods according to steps S4, S6 and S8.
- 35 A word that shows the assignment in accordance with step S14 is the English word "accumulated":

GR 99 P 2739

- 11 -

Graphemes: a c c u m u l a t e d
Phonemes: x k y u m y x l e t I d

- In the case of this word, the phonemes "y" and "u" or
5 "y" and "x" are initially replaced by the phoneme units
"yu" and "yx", respectively. Since these phoneme units
have already been determined in the preceding steps,
use is made in step S14 of the option that it is also
possible to take account of the grapheme units, and so
10 the grapheme unit "cc" is used for the two graphemes
"c" and "c". The pairwise assignments of the individual
graphemes or grapheme units to the individual phonemes
or phoneme units yields a correct assignment.
- 15 If no use is made of the option of taking account of
the grapheme units then, as is the case in step S6, the
individual graphemes are assigned to the individual
phonemes or phoneme units, an assignment contradicting
the previous assignments occurring in the present case
20 with the assignment of the grapheme "c" to the phoneme
unit "yu". This contradictory assignment is
established, and the grapheme "c" is combined with the
preceding grapheme "c" to form "cc". This leads, in
turn, to a correct assignment of the graphemes to the
25 phonemes.

- A check is made, in turn, in step S15 as to whether
contradictory assignments have arisen. If such
contradictory assignments are established, they are
30 erased together with the further assignments of the
respective word.

The method is terminated with the step S16.

- 35 The number of the contradictory assignments determined
in step S15 is a feature of the quality of the
conditioning of the initial database, obtained by the
method, with the individual grapheme/phoneme
assignments.

It was already possible for the method according to the invention to be used very successfully in automatically setting up a database for the German language, an assignment database with a total of 47 phonemes and 92 graphemes having been constructed. In setting up the database for the English language, which has a substantially more complicated grapheme/phoneme assignment, 62 phonemes and 222 graphemes resulted whose assignments are not as good as in the case of the German language. The larger number of graphemes in the English language complicates their processing. It can therefore be expedient to introduce a zero phoneme, that is to say a phoneme without a sound. Such a zero phoneme can be assigned, for example, to the English grapheme unit "gh", which occurs in the English language in a voiceless fashion in combination with the graphemes "ei", "ou" and "au". If no such zero phoneme was introduced, it would be necessary for the phonemes "eigh", "ough" and "augh" to be introduced in addition to the graphemes "ei", "ou" and "au". The zero phoneme permits a reduction in the number of the graphemes, since "eigh", "ough" and "augh" can be replaced respectively by "ei", "ou" and "au" in combination with "gh". The reliability of the method can be raised thereby. In particular, a smaller number of phonemes and/or graphemes permits a simpler, faster and more reliable application in the case of a neural network that is trained by means of the database set up with the aid of the method according to the invention.

Such a neural network, which has five input nodes and two output nodes, is illustrated schematically in a simplified fashion in figure 2. Three consecutive letters B1, B2 and B3 of a word that is to be converted into phonemes are input at three of the five input nodes. There are two nodes on the output side, one of the two outputting the respective phoneme Ph, and the other node outputting a grouping Gr. The grouping GR, last output

and the phoneme Ph_1 last output are input at the two further input nodes.

5 This network is trained with the words of the database
conditioned using the method according to the
invention, the grapheme/phoneme assignments of which
database do not constitute a contradiction to the
remaining grapheme/phoneme assignments, that is to say
the words whose graphemes could be correctly assigned
10 to the phonemes.

The neural network determines a phoneme for the middle
letter B_2 in each case, account being taken of the
respectively preceding letter and subsequent letter in
15 the context, and of the phoneme Ph_1 preceding the
phoneme to be determined. If the two consecutive
letters B_2 and B_3 constitute a grapheme unit, the
result is an output of two for the grouping Gr . If the
letter B_2 is not a constituent of a grapheme unit
20 consisting of a plurality of letters, a one is output
as grouping Gr .

Account is taken of the respectively last grouping Gr ,
on the input side, no phoneme Ph being assigned to the
25 middle letter B_2 in the case of a grouping of Gr_1 of
two, since this letter has already been taken into
account with the last grapheme unit. The second letter
of the grouping is skipped in this case.

30 During training of the neural network, the values for
the input nodes and for the output nodes are, as is
known per se, prescribed for the neural network, as a
result of which the neural network acquires the
respective assignments in the context of the words.

35

It can be expedient to provide more than three letters
at the input side the neural network, in particular in
the case of languages such as the English language in

10069941 .061902

GR 99 P 2739

- 13a -

which a plurality of letters are used to represent a
single

sound. For the German language it is expedient to provide three or five nodes at the input side for inputting letters, whereas for the English language five, seven or even nine nodes can be expedient for
5 inputting letters. Grapheme units with up to five letters can be handled given nine nodes.

Once the neural network has been trained with the database according to the invention, it can be used for
10 generating language automatically. A device for generating language in which the neural network according to the invention can be used is shown schematically in figure 3.

15 This device is an electronic data processing device 1 with an internal bus 2, to which a central processor unit 3, a memory unit 4, an interface 5 and an acoustic output unit 6 are connected. The interface 5 can make a connection to a further electronic data processing
20 device via a data line 8. A loudspeaker 7 is connected to the acoustic output unit 6.

The neural network according to the invention is stored in the memory unit 4 in the form of a computer program
25 that can be run by means of the central processor unit 3. A text which is fed to the electronic data processing device in any desired way, for example, via the interface 5, can then be fed with the aid of an appropriate auxiliary program to the neural network
30 that converts the graphemes or letters of the text into corresponding phonemes. These phonemes are stored in a phoneme file that is forwarded via the internal bus 2 to the acoustic output unit 6 with the aid of which the individual phonemes are converted into electric signals
35 that are converted into acoustic signals by the loudspeaker 7.

The method according to the invention for conditioning a database can also be designed with the aid of such an electronic processing device 1, the method being stored, again, in the form of a computer program in the
5 memory 4, and being run by the central processor unit 3, in which case it conditions an initial database that represents a dictionary in script and phonetic transcription, into a database in which the individual sounds, the phonemes, are assigned to the individual
10 letters or letter combinations, the graphemes.

The assignment of the individual graphemes to the individual phonemes can be stored in the conditioned database by blank characters that are inserted between
15 the individual phonemes and graphemes.

The computer programs representing the method according to the invention and the neural network can also be stored on any desired electronically readable data
20 media, and thus be transmitted to a further electric data processing device.

The invention is described above with the aid of an exemplary embodiment with the aid of which a database
25 for speech synthesis is generated. Of course, it is also possible within the scope of the invention to use the database generated according to the invention in speech recognition, since speech recognition methods frequently use databases with grapheme/phoneme
30 assignments.

Speech recognition can be executed, for example, with the aid of a neural network that has been trained with the database set up according to the invention. At the
35 input side, this neural network preferably has three input nodes at which the phoneme converted into a grapheme is input and, if it is present, at least one phoneme preceding in the word and one subsequent phoneme are input. At the output

GR 99 P 2739

- 16 -

side, the neural network has a node at which the grapheme assigned to the phoneme is output.

Thus, the scope of the invention covers any application
5 of the setting up and use of the database set up according to the invention in the field of automatic speech processing.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.